

e-STUDIO 477s/527s



- Fast printing
up to 52 ppm B&W
- Latest e-BRIDGE controller
- Advanced LED printing
- Colour Scanning
- Banner printing
- Small footprint



Compact size. Endless possibilities.

TOSHIBA
beyond workflow

Specifications

GENERAL

Type	Desktop
Maximum original paper size	Folio (Legal)
Print/copy speed (A4)	47/52 ppm
Paper input capacity (80g/m ² , A4)	Standard: 530 sheets (Drawer), 100 sheets (Stack Feed Bypass) Optional: 530 sheets (PFU) x 3, 2,000 sheets (LCF) Note: Paper input capacity depends on system configuration. Drawers: A5 - Folio (Standard size), 148 x 210mm - 216 x 356mm (Custom size), 64 - 220g/m ² Stack Feed Bypass: A6 - Folio (Standard size), 64 x 127mm - 216 x 1,321mm (Custom size), 64 - 250g/m ²
Paper size & weight	160GB (Security HDD)/2GB Approx. 35 sec. Max. 1.5kW (220-240V) 522 x 564 x 811mm Approx. 47kg
Hard disk drive/Memory	
Warm-up time	
Power consumption	
Dimensions (W x D x H)	
Weight	

COPYING FUNCTIONS

Original size	A6 - Folio
Copy size	Drawers: A5 - Folio, Custom size, SFB: A6 - Folio, Custom size
Resolution	Scanning: 600 x 600 dpi Printing: 600 x 600 dpi
Original scanning speed	52 spm
First copy time	8.0 sec.
Multiple copies	Up to 999 sheets
Original Mode	Text, Text/Photo, Photo
Reproduction Ratio	25% to 400% (1% Increment) (Glass) 25% to 200% (1% Increment) (Original on RADF) Automatic/Manual (11 steps)
Exposure control	
Major features	
•2 in 1/4 in 1/8 in 1(Duplex) •Annotation •X-Y Zoom•Trimming/Masking	
•Magazine Sort •Job Reservation •Job Build •Image Shift	
•Proof Copy •Image Adjustment •Background Adjustment •Sharpness Adjustment	
•Omit Blank Page •Original Outside Erase	

PRINTING FUNCTIONS

Print engine resolution	Max. 600 x 600 dpi, 1200 x 1,200 dpi (PS only)
Supported OS	Windows XP (32bit/64bit)/2003 server (32bit/64bit)/ Vista SP2 (32bit/64bit)/2008 server (32bit/64bit)/ Server 2008 R2(64bit)/7 (32bit/64bit)/8 (32bit/64bit) Server 2012(64bit) Mac OS X 10.4 or later UNIX (SUN Solaris 2.6, 2.7, 7.8, 8, 9, 10, HP-UX (10.20, 11x), IBM AIX (4.3.3), Linux, SCO) Standard: 10/100/1000baseT Option: IEEE802.11b/g/n (Wireless LAN module) TCP/IP (IP v4/v6), IPX/SPX, EtherTalk, NetBIOS over TCP/IP Windows Printing, LPR/LPD, IPP, NetWare P-SERVER, Apple Talk PAP or EtherTalk, Port 9100, WS Print, FTP PCL6 Emulation, PostScript3 Emulation, XPS
Interface	
Network protocols	
Printing protocols	
PDL	
Major features	
•Scheduled Print •Private Print •Proof Print •Watermark Printing •N-up Printing	
•Magazine Sort •Image Overlay •Booklet Printing •Hold Print •Save to Box (e-filing)	
•Poster Print •USB direct printing	

SCANNING FUNCTIONS

Scanning speed (A4)	B&W: 52 spm A4 (all resolution) Colour: 40 spm (up to 300dpi), 25 spm (at 400/600dpi)
Scanning mode	Auto Colour, Full Colour, Grayscale, Black
File format	B&W: TIFF, PDF, XPS Grayscale/Colour: JPEG, TIFF, PDF, Slim PDF, XPS Auto Colour: TIFF, PDF, XPS
Scanning resolution	600/400/300/200/150/100 dpi
Major features	
•2-sided Scan •Image Rotation •Mixed Size Paper Scanning •Scan to Email	
•Scan to file (SMB, FTP, FTPS, IPX/SPX, NetWare over TCP/IP) •Scan to e-Filing •Scan to USB	
•Preview •WS Scan •Omit Blank Page •Original Outside Erase	

ELECTRONIC FILING FUNCTIONS

User box	200
Number of folders	100 folders per Box
Number of documents	400 documents per Box/Folder
Number of pages	200 pages per document
Input to box (Multi agent)	Copy & Box, Print & Box, Received Fax to file & Box, Received I-fax to File & Box (w/o Sub No.), Received Fax to Email & Box, Received Fax to Fax/I-fax relay & Box, Received I-fax to I-fax reply & Box, Fax to Mailbox & Box, Scan to file & Box, Scan to email & Box
Box N/W access applications	TWAIN driver, File Downloader

INTERNET-FAX/NETWORK-FAX FUNCTIONS

Compatibility	T.37 (Simple Mode)
Support OS (Network Fax Drivers)	Windows XP (32bit/64bit)/2003 server (32bit/64bit)/ Vista SP2 (32bit/64bit)/2008 server (32bit/64bit)/ Server 2008 R2 (64bit)/7 SP1 (32bit/64bit)/8 (32bit/64bit) Server 2012 (64bit)

NETWORK/DEVICE MANAGEMENT UTILITY

• TopAccess • TopAccess DocMon • Address Book Viewer • e-BRIDGE Fleet Management System (Opt.)

REVERSING AUTOMATIC DOCUMENT FEEDER (STANDARD)

Available original size & weight	100 sheets
Original setting	Face-up
Available original size & weight	A6 - Folio, 60-105g/m ² (single sided/double sided)

AUTOMATIC DUPLEXING UNIT (STANDARD)

Stack capacity	No limit (stackless type)
Paper size	A5-A4
Available original size & weight	64-220g/m ²

DISTRIBUTED BY

OPTIONS

Finisher MJ-1038	
Paper Capacity (80g/m ²)	Approx. 500 sheets (A4)
Staple Capacity (80g/m ²)	50 sheets (A4) 30 sheets (FOLIO)
Staple	STAPLE-2000
Staple Position	Single/front
Dimensions (W x D x H) & Weight	386.7 x 565.5 x 214.8mm, Approx. 8.3kg
Offline Stapler MJ-1039	
Staple Capacity (80g/m ²)	20 sheets
Staple	STAPLE-3700
Staple Position	Single/corner
Dimensions & Weight	Embedded in main unit
Paper Feed Unit MY-1046	
Paper supply (80g/m ²)	Approx. 530 sheets
Paper size & weight	A5-Folio (64 - 220 g/m ²)
Dimensions (W x D x H)	522 x 485 x 136 mm
Weight	7.3kg
FAX Unit GD-1340	
Compatibility	Super G3, G3
Number of lines	1 line
Modem speed	Max. 33.6k bps
Data compression method	JBIG, MMR, MR, MH
Communication protocols	ITU-T T.30
Transmission speed	Approx. 3 seconds
Scanning mode	Text, Text/Photo, Photo (B&W only)
Gray scale	256 steps
Spacer GR-1160	
Caster GR-1170	
Desk MH-3400	

•Wireless LAN Module GN-1060 •Antenna GN-3010 •Data Overwrite Enabler GP-1070 •IPSec Enabler GP-1080 •Unicode Front Enabler GS-1007 •Meta Scan Enabler GS-1010 •e-BRIDGE ID Gate KP-2004 for HID/KP-2005 for MIFARE •Harness Kit For Coin Controller GQ-1260

Software

e-BRIDGE Re-Rite™
e-BRIDGE Fleet Management System
e-BRIDGE Connector for Google™ Docs
e-BRIDGE Connector for Microsoft® SharePoint
e-BRIDGE Connector for HP TRIM software®
e-BRIDGE Connector for Microsoft® Exchange
e-BRIDGE Capture & Store Essentials edition
e-BRIDGE Accounts
e-BRIDGE Job Separator eX driver plugin
e-BRIDGE Job Build eX driver plugin
e-BRIDGE Replicator eX driver plugin
e-BRIDGE Job Point eX driver plugin
e-BRIDGE Mac Fax
e-BRIDGE PC Fax

ISO 9001 and ISO 14001 Certifications

These highly acclaimed certifications are recognised worldwide as measures of top quality and environmental management excellence. They are awarded to manufacturers for facilities and practices meeting strict standards set by the Geneva based International Standardization Organization. To date, four copier sales affiliates and all Toshiba TEC manufacturing facilities where copiers, accessories, supplies and parts are produced have received ISO 9001 certification, while four copier sales affiliate and all Toshiba TEC manufacturing facilities have received ISO 14001 certification — even more reasons to count on Toshiba.

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries. Adobe® PostScript® Level 3™ is a registered trademark of Adobe Systems, Inc. Mac OS® is a registered trademark of Apple Inc. Google Docs is a registered trademark of Google Inc. HP TRIM software™ is a registered trademark of Hewlett-Packard. All other brand and/or product names are trademarks of their respective owners.

This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. *1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed. Days for function availability may differ by region. "e-filing" is an abbreviation of "electronic filing". Warm-up time and print speed may vary depending on the operating environment. ©2013 TOSHIBA TEC CORPORATION All rights reserved.

As an ENERGY STAR Partner TOSHIBA TEC CORPORATION has determined that this multifunctional device model meets the ENERGY STAR guidelines for energy efficiency.



TOSHIBA (AUSTRALIA) PTY LIMITED
ABN 19 001 320 421
Building C, 12-24 Talavera Road, North Ryde, NSW 2113
Tel: (02) 9887-6000 Fax: (02) 9815-6274
New Zealand Office
58 Lunn Avenue, Mt Wellington, Auckland, NZ
Tel: (9) 570-8530 Fax: (9) 570-8930
www.eid.toshiba.com.au
www.eid.toshiba.co.nz

